



I/O Modules Overview

Use these instructions to set up the I/O modules supported in your TippingPoint security devices.

Before You Begin

- Review the release notes for your product for any late-breaking changes to the installation instructions.
- Read and follow all safety information listed in documentation that shipped with your product.
- Complete the installation of your TippingPoint security device.

ESD Requirements

Damage from Electromagnetic Static Discharge (ESD) can occur when electronic components are improperly handled. Improper handling can result in complete or intermittent system failures. Proper ESD protection is required whenever you handle equipment. The following general grounding guidelines apply:

- Always use an ESD wrist strap when adding or removing components from the chassis.
- Avoid touching the circuit boards or connectors on all cards and modules.
- Avoid contact between the printed circuit boards and clothing. The wrist strap only protects components from ESD voltages on the body. ESD voltages on clothing can still cause damage.

Place a removed component board-side-up on an antistatic surface or in a static-shielding container that is also grounded to the same point as the device. If you plan to return the component to the factory, immediately place it in a static-shielding container.

I/O Module Options

TippingPoint devices with module slots support both standard I/O modules and bypass I/O modules (refer to the following table) for fiber and copper components.

Important: Only optical transceiver modules (including SFP, SFP+, and QSFP+) available from TippingPoint have been validated to achieve optimal performance with TippingPoint products. Other vendor devices are not supported and could be detrimental to proper operation of the TippingPoint system.

Bypass I/O modules are zero-power high-availability (ZPHA) modules that permit network traffic and services while bypassing the device entirely when the device loses power. All four standard I/O

modules and all five bypass I/O modules are hot-swappable on devices running TippingPoint Operating System (TOS) v3.6.0 or higher.

For more information on I/O modules, refer to the product hardware documentation for your device.

Standard I/O Modules

6-Segment Gig-T



Ports: 12 Fixed RJ-45 copper ports
Port speed: 10/100/1000 Mbps
Part number: TPNN0059

6-Segment GbE SFP



Ports: 12 SFP ports
Port speed: 1 Gbps
Part number: TPNN0068

4-Segment 10GbE SFP+



Ports: 8 Fiber SFP+ ports
Port speed: 10 Gbps
Part number: TPNN0060

1-Segment 40 GbE QSFP+



Ports: 2 Fiber QSFP+ ports
Port speed: 40 Gbps
Part number: TPNN0069

Bypass I/O Modules

4-Segment Gig-T Bypass Module



Ports: 8 copper ports
Port speed: 10/100/1000 Mbps
Part number: TPNN0070

2-Segment 1G Fiber SR/LR Bypass Module



Ports: 4 Multi-Mode (SR)/Single-Mode (LR) Fiber (LC type)
Port speed: 1 Gbps
Part number: TPNN0071/TPNN0072

2-Segment 10G Fiber SR/LR Bypass Module



Ports: 4 Multi-Mode (SR)/Single-Mode (LR) Fiber (LC type)
Port speed: 1/10 Gbps
Part number: TPNN0073/TPNN0074

Important: Handle all I/O modules with care. The bypass modules contain mechanical switches that are very delicate and can cause network disruption if handled improperly. For more information about deploying bypass modules, refer to the product hardware documentation for your TippingPoint security device.

Add I/O Modules

TippingPoint devices come with blank modules inserted into module slots.



To remove the blank module, slide the slide latch (1) to the right and pull on the handle (2 on left module) or grab point (2 on right module).

CAUTION: Never lift your device using the module handles.



To insert an I/O module, slide the module into the empty module slot. When the module is in the correct position, the slide latch automatically slides into position.

Warning: Do not leave slots empty for an extended period of time. Insertion of a blank module or I/O module ensures that the device is correctly cooled.

Module LEDs

The following table describes the module LEDs.

Feature	LED	Color	Description
Fixed RJ45 copper port	Link	Green	Link is active.
	Activity	Blinking amber	Data traffic passing.
Optical transceiver port	Link	Green	Link is active.
	Activity	Amber	Data traffic passing.

Feature	LED	Color	Description
Module Health 	Status	Green	The module is configured, in service, and in good health.
		Blinking amber	The module has been inserted and powered up, but is not yet recognized by the software.
		Solid amber	The module is experiencing a fault.
Bypass 	Status	Off	Module in bypass.
		Green	Module in normal mode (not in bypass).

Hot-Swapping I/O Modules

On devices running TOS v3.6.0 or higher, I/O modules can be installed or removed while the device is in the normal operating state. *Hot-swapping I/O modules during system initialization is not supported.* There are several slot and port configuration factors to consider when hot-swapping I/O modules. For detailed guidelines and procedures, refer to the product hardware documentation for your TippingPoint security device.

Supported Transceivers and Cables for TippingPoint I/O Modules

I/O module & part number	Transceiver part number	Transceiver name
6-Segment GbE SFP (TPNN0068)	TPNN0054	TippingPoint X126 1G SFP RJ45 Transceivers (Copper and Fiber)
4-Segment 10GbE SFP+ (TPNN0060)	TPNN0057	TippingPoint S136 10G SFP+ LC SR Transceiver
	TPNN0058	TippingPoint S136 10G SFP+ LC LR Transceiver
	TPNN0054	TippingPoint X126 1G SFP RJ45 Transceivers (Copper and Fiber)
1-Segment 40 GbE QSFP+ (TPNN0069)	TPNN0067	TippingPoint S146 40G QSFP+ SR4 850nm Transceiver
	TPNN0327	TippingPoint S146 40G QSFP+ LR4 1310nm Transceiver

I/O module part number	Cable part number	Cable name
TPNN0069*	TPNN0212	TippingPoint 40G QSFP+ Active Optical Cable (AOC)

*When this I/O module is used with this cable, transceivers TPNN0067/TPNN0327 are not needed. The cable has the transceiver attached.

Privacy and Personal Data Collection Disclosure

Certain features available in Trend Micro products collect and send feedback regarding product usage and detection information to Trend Micro. Some of this data is considered personal in certain jurisdictions and under certain regulations. If you do not want Trend Micro to collect personal data, you must ensure that you disable the related features.

The following link outlines the types of data that the Security Management System collects and provides detailed instructions on how to disable the specific features that feedback the information.

<https://success.trendmicro.com/data-collection-disclosure>

Data collected by Trend Micro is subject to the conditions stated in the Trend Micro Privacy Policy:

https://www.trendmicro.com/en_us/about/legal/privacy-policy-product.html

Legal Notice

© Copyright 2018 Trend Micro Incorporated. All rights reserved.

Trend Micro, the Trend Micro t-ball logo, TippingPoint, and Digital Vaccine are trademarks or registered trademarks of Trend Micro Incorporated. All other product or company names may be trademarks or registered trademarks of their owners.

Publication: September 2018